

View Online at <https://aerobasegroup.com/nsn/5930-00-448-5324>

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.550 inches

Overall Height:

3.160 inches

Overall Width:

5.120 inches

Mounting Slot Width:

0.203 inches

Capillary Tube Length:

24.0 inches

Bulb Length:

7.500 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

1.266 inches

Longest Vertical Distance Between Mounting Centers:

2.000 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Mounting Method:

Bracket and slot

Features Provided:

Capillary tube end seal connection

Contact Action Stimulus:

Decrease

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

5.8 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+60.00/+90.00 actuation point degrees fahrenheit and +60.00/+90.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point shaft and external actuation point shaft

Contact Voltage Rating In Volts:

120.0 ac at sea level single voltage

Special Features:

6 slots, 3 slots on opposite of 2 sides and spaced in line 1.000 in. Apart and 1.266 in. Centers

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0