## NSN 5930-00-448-6661



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-448-6661 **Body Style:** Panel mount **Hazardous Locations/environmental Protection:** Moisture proof **Overall Length:** 0.750 inches **Overall Height:** 3.060 inches **Overall Width:** 0.750 inches **Body Length:** 0.740 inches **Body Width:** 0.740 inches **Case Material:** Metal **Actuator Length:** 0.740 inches **Actuator Style:** Rectangular **Actuator Width:** 0.740 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Nonpile-up Contact Arrangement:** 4 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac **Precious Material And Location:** Contact surfaces gold and contacts silver **Unable To Decode:** Unable to decode and unable to decode **Terminal Type And Quantity:** 17 pin Shelf Life:

No

N/a

**Unit Of Measure:** 

Demilitarization:

## NSN 5930-00-448-6661

Push Switch - Page 2 of 2



Fiig:

A053a0