## NSN 5930-00-448-6661

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-448-6661

## **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Moisture proof

## **Overall Length:**

0.750 inches

### **Overall Height:**

3.060 inches

#### **Overall Width:**

0.750 inches

#### **Body Length:**

0.740 inches

#### **Body Width:**

0.740 inches

#### Case Material:

#### Metal

#### Actuator Length:

0.740 inches

## Actuator Style:

Rectangular

## Actuator Width:

0.740 inches

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Inclosure Type:

Fully enclosed

#### **Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac and 1.500 amperes lamp ac

#### **Precious Material And Location:**

Contact surfaces gold and contacts silver

#### Unable To Decode:

Unable to decode and unable to decode

## Terminal Type And Quantity:

17 pin

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5930-00-448-6661

Push Switch - Page 2 of 2

Fiig: A053a0

