

View Online at <https://aerobasegroup.com/nsn/5930-00-448-7475>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

1.558 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.315 inches

**First Flat Length:**

0.375 inches single actuator

**Flat Height:**

0.198 inches single actuator and 0.201 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.687 inches single actuator

**Nonturn Device Radius:**

0.422 inches at 3:00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 3:00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

240.0 ac at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, slotted, flatted single actuator

**Terminal Type:**

Quick disconnect, male

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

25.0 amperes resistive load ac at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0