NSN 5930-00-448-9575

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-448-9575 **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Body Diameter:** 0.625 inches **Bushing Length:** 0.312 inches **Body Length:** 0.906 inches **Actuator Diameter:** 0.500 inches **Actuator Height:** 0.570 inches **Actuator Color:** Red single actuator **Illuminated Actuator Color:** Red single actuator **Maximum Voltage Rating In Volts:** 125.0 ac and 30.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 2.000 amperes resistive dc and 2.000 amperes resistive ac **Thread Series Designator:** Uns **Terminal Type And Quantity:** 8 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5930-00-448-9575

Push Switch - Page 2 of 2



Fiig:

A053a0