

View Online at <https://aerobasegroup.com/nsn/5930-00-448-9823>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.380 inches single mounting facility

**Overall Length:**

2.440 inches

**First Flat Length:**

0.480 inches single actuator

**Flat Height:**

0.190 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

0.560 inches single actuator

**Overall Diameter:**

2.310 inches

**Nonturn Device Radius:**

0.530 inches at 3: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Operating Temperature Range:**

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section rear

**Throw Quantity:**

23 each section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

30.0 dc at altitude

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

24 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load dc at altitude

**Precious Material And Location:**

Contacts and rotors silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0