NSN 5930-00-449-1657

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-449-1657

, , , , , , , , , , , , , , , , , , , ,
Overall Length:
1.739 inches
Overall Height:
2.370 inches
Overall Width:
1.020 inches
Body Height:
1.320 inches
Unthreaded Mounting Hole Diameter:
Between 0.150 inches and 0.155 inches
Longest Horizontal Distance Between Mounting Centers:
0.754 inches
Longest Vertical Distance Between Mounting Centers:
0.754 inches
Pressure Switch Type:
Differential
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 200.0 degrees fahrenheit
Mounting Method:
Unthreaded hole
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch gage
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
2 pole, double throw, both positions maintained
Sensing Element Burst Pressure:
7500.00 pounds per square inch gage
Terminal Type:
Pin
Contact Load Current Rating:
2.5 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable, manual reset and actuation point not adjustable
Contact Stimulus Rating:
37.40 deactuation point pounds per square inch gage
Contact Voltage Rating In Volts:
36.0 dc at sea level third voltage
3

ricquency minera

60.0 first voltage

NSN 5930-00-449-1657

Pressure Switch - Page 2 of 2



N	lec	lia	а	F	or	W	hi	ch	ı D	es	ig	ne	ed	:

Liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0