

View Online at <https://aerobasegroup.com/nsn/5930-00-449-6921>

Thread Class:

2a all threaded hole

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.563 inches

Overall Height:

2.610 inches

Overall Width:

1.250 inches

Distance Between Mounting Facility Centers:

Between 2.179 inches and 2.195 inches

Capillary Tube Length:

30.0 inches

Temperature Sensing Element Type:

Capillary tube

Mounting Method:

Bracket and threaded hole

Features Provided:

Automatic reset

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Decrease

Thread Size:

0.164 inches all threaded hole

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

8.3 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable, preset

Contact Adjustment Range:

+12.00/+38.00 actuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point knob

Contact Stimulus Rating:

17.00 actuation point degrees fahrenheit and 23.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Media For Which Designed:

Gas

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0