

View Online at <https://aerobasegroup.com/nsn/5930-00-450-1155>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.688 inches

**Body Length:**

2.250 inches

**Body Width:**

2.562 inches

**Body Height:**

7.062 inches

**Unthreaded Mounting Hole Diameter:**

0.260 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

6.406 inches

**Actuator Style:**

Round

**Actuator Height:**

0.500 inches

**Maximum Voltage Rating In Volts:**

600.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

298.0 inch-ounces

**Switch Actuating Force:**

288.0 inch-ounces

**Actuator Movement:**

90.0 pretravel degrees and 90.0 overtravel degrees and 4.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

750.000 milliamperes resistive dc and 2.500 amperes resistive ac

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0