

View Online at <https://aerobasegroup.com/nsn/5930-00-450-1166>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

4.344 inches

**Overall Height:**

4.563 inches

**Overall Width:**

3.500 inches

**Body Length:**

3.282 inches

**Distance Between Mounting Facility Centers:**

2.250 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

160.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

500.0 milliamperes resistive load third voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+3.90/+80.00 actuation point pounds per square inch gage and +0.50/+76.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0