NSN 5930-00-450-5328

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-450-5328

Inside Diameter:
0.125 inches single connection
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
5.250 inches
Overall Height:
2.500 inches
Overall Width:
3.188 inches
Body Length:
3.000 inches
Longest Horizontal Distance Between Mounting Centers:
2.625 inches
Longest Vertical Distance Between Mounting Centers:
2.438 inches
Pressure Switch Type:
Gage
Mounting Method:
Inlet connection and unthreaded hole
Features Provided:
Automatic reset
Contact Action Stimulus:
Increase
Proof Pressure:
400.00 pounds per square inch
Thread Size:
0.125 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Threaded stud
Contact Load Current Rating:
10.0 amperes inductive load first voltage
Contact Adjustability:
Actuation point adjustable and deactuation point not adjustable
Contact Adjustment Range:
+3.50/+90.00 actuation point pounds per square inch and +3.00/+85.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point hex nut and external deactuation point hex nut

NSN 5930-00-450-5328

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage **Pressure Connector Type:** Plain, threaded internal single connection Frequency In Hertz: 60.0 first voltage Media For Which Designed: Gas or liquid Style Designator: Rectangular **Thread Series Designator:** Npt single pressure connection Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A048b0