

View Online at <https://aerobasegroup.com/nsn/5930-00-450-5328>

Inside Diameter:

0.125 inches single connection

Hazardous Locations/environmental Protection:

Weatherproof

Overall Length:

5.250 inches

Overall Height:

2.500 inches

Overall Width:

3.188 inches

Body Length:

3.000 inches

Longest Horizontal Distance Between Mounting Centers:

2.625 inches

Longest Vertical Distance Between Mounting Centers:

2.438 inches

Pressure Switch Type:

Gage

Mounting Method:

Inlet connection and unthreaded hole

Features Provided:

Automatic reset

Contact Action Stimulus:

Increase

Proof Pressure:

400.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Threaded stud

Contact Load Current Rating:

10.0 amperes inductive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point not adjustable

Contact Adjustment Range:

+3.50/+90.00 actuation point pounds per square inch and +3.00/+85.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point hex nut and external deactuation point hex nut

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0