

View Online at <https://aerobasegroup.com/nsn/5930-00-450-5374>

Overall Diameter:

4.188 inches

Unthreaded Mounting Hole Diameter:

0.219 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.376 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.188 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.063 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

10 each section front

Mounting Method:

Base single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

300.0 ac at sea level

Rotor Through Connection Quantity:

1 each section

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

10 single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0