

View Online at <https://aerobasegroup.com/nsn/5930-00-450-5402>

**Thread Class:**

2b all pressure connection

**Inside Diameter:**

0.250 inches all connections

**Thread Length:**

0.375 inches all pressure connection

**Overall Length:**

1.656 inches

**Body Length:**

1.031 inches

**Overall Diameter:**

3.000 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Inlet connection

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Threaded stud

**Contact Load Current Rating:**

1.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

8.00 actuation point inches of water and 7.00 deactuation point inches of water and 1.00 differential point inches of water

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Pressure Connector Type:**

Double compression, threaded internal all connections

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Thread Series Designator:**

Unc all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0