

View Online at <https://aerobasegroup.com/nsn/5930-00-450-6155>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.997 inches and 1.003 inches

**Overall Width:**

0.740 inches

**Body Width:**

0.740 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.140 inches and 0.144 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 0.633 inches and 0.647 inches

**Actuator Roller Diameter:**

Between 0.209 inches and 0.213 inches

**Actuator Roller Width:**

Between 0.154 inches and 0.158 inches

**Actuator Adapter Style:**

Roller arm

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

48.0 ounces

**Actuator Movement:**

Between 0.075 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 1.000 amperes inductive dc

**Special Features:**

Wire leads 48 inches lg

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0