NSN 5930-00-450-6349

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-450-6349

9	
Body Style:	
Hole mounted	
Hazardous Locations/environmental Protection:	
Dustproof	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
1.000 inches	
Body Length:	
1.938 inches	
Body Width:	
0.688 inches	
Body Height:	
0.797 inches	
Unthreaded Mounting Hole Diameter:	
0.140 inches	
Actuator Length:	
1.906 inches	
Actuator Style:	
Roller arm	
Actuator Free Position Height:	
1.188 inches	
Actuator Roller Diameter:	
0.375 inches	
Actuator Roller Width:	
0.156 inches	
Maximum Voltage Rating In Volts:	
250.0 ac	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Unthreaded hole	
Features Provided:	
Actuator seal	
Nonpile-up Contact Arrangement:	
1 pole, double throw, both positions maintained single switch unit	
Switch Release Force:	
0.5 ounces	
Switch Actuating Force:	

Actuator Movement:

2.5 ounces

Between 0.469 pretravel inches and 0.062 overtravel inches and 0.085 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes resistive ac

NSN 5930-00-450-6349

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0