NSN 5930-00-451-5270

Rotary Switch - Page 1 of 2

Thread Class:

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-451-5270

Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.000 inches **Overall Height:** 1.875 inches **Overall Width:** 2.812 inches First Flat Length: 0.875 inches single actuator Flat Height: 0.216 inches single actuator **Shaft Diameter:** 0.248 inches single actuator and 0.251 inches single actuator **Shaft Length:** 1.375 inches single actuator **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 single section rear **Throw Quantity:** 5 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 60.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator

NSN 5930-00-451-5270

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

7.5 amperes resistive load ac at sea level

Precious Material And Location:

Terminals silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0