

View Online at <https://aerobasegroup.com/nsn/5930-00-451-5571>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

7.646 inches

**Overall Height:**

2.312 inches

**Overall Width:**

1.968 inches

**Shaft Diameter:**

0.375 inches 1st actuator

**Shaft Length:**

0.563 inches 2nd actuator

**Nonturn Device Radius:**

0.531 inches at 10: 30 o'clock

**Individual Section Quantity:**

7

**Nonturn Device Type:**

Tab at 10: 30 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Pole Quantity:**

2 5th section rear

**Throw Quantity:**

8 1st section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.625 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

28 all actuators

**Shaft Type:**

Round, hollowed 1st actuator

**Terminal Type:**

Clip

**Contact Switching Action:**

Makes before breaks each section rear

**Switch Actuator Positioning Increment:**

12.85 degrees all actuators

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Special Features:**

Section 2 has 9 dummy terminals on rear; section 3 has 2 dummy terminals on rear; section 4 has 2 dummy terminals on rear; section 5 has 1 dummy terminal on front and 11 dummy terminals on rear; section 6 has 1 dummy terminal on rear; section 7 is operated by 2nd shaft and has 2 dummy terminals on rear

**Precious Material And Location:**

Contact and rotor blade surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0