

View Online at <https://aerobasegroup.com/nsn/5930-00-451-5571>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

7.646 inches

Overall Height:

2.312 inches

Overall Width:

1.968 inches

Shaft Diameter:

0.375 inches 1st actuator

Shaft Length:

0.563 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 10: 30 o'clock

Individual Section Quantity:

7

Nonturn Device Type:

Tab at 10: 30 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

2 5th section rear

Throw Quantity:

8 1st section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.625 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

28 all actuators

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Clip

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

12.85 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Special Features:

Section 2 has 9 dummy terminals on rear; section 3 has 2 dummy terminals on rear; section 4 has 2 dummy terminals on rear; section 5 has 1 dummy terminal on front and 11 dummy terminals on rear; section 6 has 1 dummy terminal on rear; section 7 is operated by 2nd shaft and has 2 dummy terminals on rear

Precious Material And Location:

Contact and rotor blade surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0