

View Online at <https://aerobasegroup.com/nsn/5930-00-451-5591>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.906 inches

Overall Height:

4.562 inches

Overall Width:

3.500 inches

Distance Between Mounting Facility Centers:

2.250 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

18 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

60.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

500.0 milliamperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.65/+18.00 actuation point pounds per square inch gage and +0.40/+17.75 deactuation point pounds per square inch gage

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0