NSN 5930-00-451-5772

Flow Switch - Page 1 of 1

Fiig: A048b0



View Online at https://aerobasegroup.com/nsn/5930-00-451-5772 **Overall Height:** 0.844 inches **Overall Width:** Between 0.531 inches and 0.593 inches **Body Length:** Between 0.646 inches and 0.666 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Longest Horizontal Distance Between Mounting Centers:** Between 0.740 inches and 0.760 inches **Longest Vertical Distance Between Mounting Centers:** Between 0.490 inches and 0.510 inches **Operating Tempurature Rating:** 55.0 degrees celsius and 0.0 degrees celsius **Mounting Method:** Strap **Contact Action Stimulus:** Increase **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 5.0 amperes resistive load single voltage **Contact Adjustability:** Deactuation point not adjustable and actuation point not adjustable **Contact Stimulus Rating:** 2270.00 actuation point feet per minute and 2035.00 deactuation point feet per minute and 235.00 differential point feet per minute **Contact Voltage Rating In Volts:** 115.0 ac at sea level single voltage Shelf Life: N/a **Unit Of Measure: Demilitarization:** No