NSN 5930-00-451-5772

Flow Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-451-5772

Overall Height:

0.844 inches

Overall Width:

Between 0.531 inches and 0.593 inches

Body Length:

Between 0.646 inches and 0.666 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Longest Horizontal Distance Between Mounting Centers:

Between 0.740 inches and 0.760 inches

Longest Vertical Distance Between Mounting Centers:

Between 0.490 inches and 0.510 inches

Operating Tempurature Rating:

55.0 degrees celsius and 0.0 degrees celsius

Mounting Method:

Strap

Contact Action Stimulus:

Increase

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

2270.00 actuation point feet per minute and 2035.00 deactuation point feet per minute and 235.00 differential point feet per minute

Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0