## NSN 5930-00-451-5976

Liquid Level Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-451-5976

| Overall Height:  |
|--|
| 6.000 inches   |
| Ac Voltage Rating:   |
| 220.0 volts 2nd operating power rqmt                       |
| Dc Voltage Rating:   |
| 6.0 volts 3rd operating power rqmt                         |
| Frequency Rating:  |
| 60.0 hertz   |
| Overall Diameter:  |
| 3.000 inches   |
| Actuation Method:  |
| Buoyancy   |
| Internal Battery Accommodation:                            |
| Not included   |
| Current Rating At Maximum Rated Voltage:                   |
| 45.0 milliamperes resistive load                           |
| Float Quantity:  |
| 1  |
| Operating Tempurature Rating:                              |
| Not rated  |
| Mounting Method:   |
| Thread   |
| Mounting Position:   |
| Vertical   |
| Maximum Current Rating:                                    |
| 500.0 milliamperes resistive load                          |
| Contact Arrangement:                                       |
| Single throw, normally open                                |
| Relay:   |
| Not included   |
| Liquid Type For Which Designed:                            |
| Fuel, nonaircraft and hydraulic oil and water              |
| Mounting Dimensions:                                       |
| Mtd by 3/4 in.Pipe thd connections at inlet and outlet     |
| Phase:   |
| Single   |
| Special Features:  |
| 24.000 in. Min, 26.000 in. Maximum Ig wire leadconnections |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

## NSN 5930-00-451-5976

Liquid Level Switch - Page 2 of 2



Demilitarization:

No

Fiig:

T109-d