

View Online at <https://aerobasegroup.com/nsn/5930-00-451-7284>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.650 inches

Overall Height:

4.880 inches

Overall Width:

1.780 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.040 inches

Actuator Roller Diameter:

0.440 inches

Housing Height:

1.780 inches

Housing Length:

2.840 inches

Housing Width:

1.560 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.340 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.160 inches

Maximum Voltage Rating In Volts:

440.0 ac and 355.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Features Provided:

Actuator seal

Thread Size:

0.190 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 inch-ounces

Switch Actuating Force:

92.0 ounces

Actuator Movement:

0.040 pretravel inches and 0.275 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 6.000 amperes resistive ac

Special Features:

Two of the four mtg holes are threaded for rear mtg

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A053a0