NSN 5930-00-451-7287

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-451-7287

| D. J. O. J. |
|---|
| Body Style: |
| Hole mounted |
| Overall Length: |
| 1.094 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.875 inches |
| Overall Width: |
| 0.400 inches |
| Body Length: |
| 1.095 inches |
| Body Width: |
| 0.400 inches |
| Body Height: |
| 0.625 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.114 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 0.406 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.110 inches |
| Actuator Free Position Height: |
| 0.578 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 10.0 grams |
| Switch Actuating Force: |
| 75.0 grams |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 500.000 milliamperes resistive dc and 10.000 amperes resistive ac |
| Special Features: |
| One mtg hole elongated to 0.126 in. |
| Precious Material And Location: |
| Contacts silver |

3 quick disconnect, male

Terminal Type And Quantity:

NSN 5930-00-451-7287

Sensitive Switch - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0