## NSN 5930-00-455-0788

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-455-0788

Thread Class:
2b single pressure connection
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.812 inches
Overall Height:
6.000 inches
Overall Width:
3.750 inches
Body Length:
3.374 inches
Distance Between Mounting Facility Centers:
2.500 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket
Features Provided:
Automatic reset
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
400.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable, preset
Contact Adjustment Range:

## Contact Adjustment Type:

Contact Adjustment Type.

Internal deactuation point hex nut and internal actuation point hex nut

+0.20/+2.00 actuation point pounds per square inch gage and +0.15/+1.65 deactuation point pounds per square inch gage

## NSN 5930-00-455-0788

Pressure Switch - Page 2 of 2

No Fiig: A048b0



## Contact Voltage Rating In Volts: 480.0 ac at sea level single voltage Pressure Connector Type: Swivel nut, compression, threaded internal single connection Media For Which Designed: Gas Style Designator: Rectangular Thread Series Designator: Npt single pressure connection Shelf Life: N/a Unit Of Measure: - Demilitarization: