

View Online at <https://aerobasegroup.com/nsn/5930-00-455-0788>

Thread Class:

2b single pressure connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

3.812 inches

Overall Height:

6.000 inches

Overall Width:

3.750 inches

Body Length:

3.374 inches

Distance Between Mounting Facility Centers:

2.500 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Features Provided:

Automatic reset

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

400.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable, preset

Contact Adjustment Range:

+0.20/+2.00 actuation point pounds per square inch gage and +0.15/+1.65 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Pressure Connector Type:

Swivel nut, compression, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0