# NSN 5930-00-455-0788

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-455-0788

# **Thread Class:**

2b single pressure connection

## Hazardous Locations/environmental Protection:

Watertight

# **Overall Length:**

3.812 inches

## **Overall Height:**

6.000 inches

## **Overall Width:**

3.750 inches

#### **Body Length:**

3.374 inches

#### **Distance Between Mounting Facility Centers:**

2.500 inches

#### Pressure Switch Type:

Gage

# Mounting Method:

Bracket

#### Features Provided:

Automatic reset

# Thready Qty Per Inch (tpi):

18 single pressure connection

# **Contact Action Stimulus:**

Increase

#### **Proof Pressure:**

400.00 pounds per square inch

## **Thread Size:**

0.250 inches single pressure connection

#### **Mounting Facility Pattern:**

Two position in-line

# Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

#### **Terminal Type:**

Connector, receptacle

#### **Contact Load Current Rating:**

15.0 amperes resistive load single voltage

# **Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable, preset

# Contact Adjustment Range:

+0.20/+2.00 actuation point pounds per square inch gage and +0.15/+1.65 deactuation point pounds per square inch gage

# Contact Adjustment Type:

Internal deactuation point hex nut and internal actuation point hex nut

# NSN 5930-00-455-0788

Pressure Switch - Page 2 of 2



**Contact Voltage Rating In Volts:** 

480.0 ac at sea level single voltage

# Pressure Connector Type:

Swivel nut, compression, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular

# **Thread Series Designator:**

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A048b0