

View Online at <https://aerobasegroup.com/nsn/5930-00-455-6505>

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Bushing Length:**

0.719 inches

**Body Length:**

1.343 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.250 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.122 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, two positions momentary single switch unit

**Switch Actuating Force:**

128.0 ounces

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0