NSN 5930-00-456-0674

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-456-0674

Thread L	_ength:
----------	---------

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

1.000 inches single actuator

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

4 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

250.0 milliamperes resistive load dc at sea level

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5930-00-456-0674Rotary Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A052b0