NSN 5930-00-456-4809

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Dustproof

Overall Length: 3.500 inches Overall Height: 4.125 inches Overall Width: 4.125 inches



View Online at https://aerobasegroup.com/nsn/5930-00-456-4809

Unthreaded Mounting Hole Diameter:			
0.250 inches single mounting facility			
Individual Section Quantity:			
1			
Knob Manufacturer Code:			
82121			
Longest Horizontal Distance Between Mounting Centers:			
2.281 inches single mounting facility			
Longest Vertical Distance Between Mounting Centers:			
2.281 inches single mounting facility			
Switch Contact Basic Design:			
Nonpile-up symmetrical			
Pole Quantity:			
2 single section front			
Throw Quantity:			
4 single section front			
Mounting Method:			
Bracket single mounting facility			
Features Provided:			
Actuator knob			
Contact Voltage Rating In Volts:			
450.0 ac at sea level			
Mounting Facility Pattern:			
Four position rectangular single mounting facility			
Switch Actuator Indexing Position Quantity:			
4 single actuator			
Terminal Type:			
Screw			
Contact Switching Action:			
Breaks before makes single section front			
Switch Actuator Positioning Increment:			
90.0 degrees single actuator			
Switch Actuator Stop Device Type:			
Fixed stop single actuator			

NSN 5930-00-456-4809

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

30.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0