NSN 5930-00-457-4462

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-457-4462
Thread Class:
3a single pressure connection
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
2.890 inches
Outside Diameter:
0.438 inches single connection
Body Diameter:
1.000 centimeters
Body Length:
3.000 inches
Overall Diameter:
1.000 inches
Pressure Switch Type:
Gage
Mounting Method:
Inlet connection
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Nonpile-up Contact Arrangement:
3 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
2.0 amperes lamp load single voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
700.00 actuation point pounds per square inch gage and 1000.00 actuation point pounds per square inch gage and 1000.00 deactuation
point pounds per square inch gage and 1300.00 deactuation point pounds per square inch gage
Contact Voltage Rating In Volts:
29.0 dc at sea level single voltage
Pressure Connector Type:
Plain, threaded external single connection
Media For Which Designed:
Gas or liquid

Cylindrical Thread Series Designator:

Style Designator:

Unjf single pressure connection

NSN 5930-00-457-4462

Pressure Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0