NSN 5930-00-457-7313

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-457-7313

Thread Length:

0.438 inches single mounting facility

First Flat Length:

0.250 inches single actuator

Flat Height:

0.093 inches single actuator

Shaft Diameter:

0.150 inches single actuator

Shaft Length:

6.125 inches single actuator

Overall Diameter:

1.088 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Rotor Through Connection Quantity:

1 single section

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Solder stud

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

NSN 5930-00-457-7313

Rotary Switch - Page 2 of 2



| Sty | ما | D | 20 | in | n | 2 | ŧ۸ | r | |
|-----|----|----|----|----|----|---|----|---|--|
| JLY | ı | יש | င၁ | ıу | •• | а | ιυ | ш | |

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0