## NSN 5930-00-457-8358



Push Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-457-8358 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Body Diameter:** 0.620 inches **Bushing Length:** 0.440 inches **Body Length:** 1.000 inches **Actuator Diameter:** 0.380 inches **Actuator Height:** 0.280 inches **Actuator Color:** Red single actuator **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.468 inches **Nonpile-up Contact Arrangement:** 1 two circuit, double break/double make, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 3.000 amperes resistive dc and 1.500 amperes inductive dc and 1.000 amperes lamp dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac and 1.000 amperes lamp ac **Thread Series Designator:** Uns **Terminal Type And Quantity:** 4 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5930-00-457-8358

Push Switch - Page 2 of 2



Fiig:

A053a0