NSN 5930-00-459-0783

Rotary Switch - Page 1 of 2



930-00-459-0783

View Online at https://aerobasegroup.com/nsn/59
Thread Class:
2a single mounting facility
Overall Length:
11.220 inches
Overall Height:
4.000 inches
Overall Width:
4.000 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
1.220 inches single actuator
Individual Section Quantity:
18
Operating Tempurature Range:
-55.0/+85.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section front
Throw Quantity:
32 each section front
Mounting Facility Circle Radius:
1.470 inches single mounting facility
Mounting Method:
Threaded bushing single mounting facility
Features Provided:
Metallic inclosure
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.164 inches single mounting facility
Contact Voltage Rating In Volts:
115.0 ac at sea level
Mounting Facility Pattern:
Three position circular single mounting facility
Switch Actuator Indexing Position Quantity:
32 single actuator
Shaft Type:
Round single actuator
Terminal Type:

Printed circuit

NSN 5930-00-459-0783

Rotary Switch - Page 2 of 2



\mathbf{c}	nnf	act	SW	itch	ina	ı Ac	tior	٠.
U	וווכ	acı	ЭW	ILCI	IIIIU	IAC	เเบเ	ı.

Breaks before makes each section front

Contact Load Current Rating:

125.0 milliamperes resistive load ac at sea level

Style Designator:

Wafer, printed board, bushing mount

Test Data Document:

81349-mils22710 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0