

View Online at <https://aerobasegroup.com/nsn/5930-00-459-3270>

Body Style:

Bushing mount

Bushing Length:

0.490 inches

Body Length:

1.340 inches

Body Width:

0.910 inches

Body Height:

1.120 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.240 inches

Actuator Height:

0.720 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

57.5 ac and 14.0 dc

Mounting Surface To Terminal End Distance:

1.370 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 7.500 amperes inductive dc and 3.500 amperes lamp dc and 7.500 amperes resistive ac and 7.500 amperes inductive ac and 2.000 amperes lamp ac

Test Data Document:

18876-10240060-2 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0