# NSN 5930-00-459-5693

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-459-5693

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.375 inches single mounting facility

## **Overall Length:**

4.937 inches

#### **Overall Height:**

1.312 inches

#### **Overall Width:**

1.188 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.875 inches single actuator

#### Nonturn Device Radius:

## 0.531 inches at 3: 00 o'clock

## Individual Section Quantity:

6

Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

## **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### **Throw Quantity:**

8 each section rear

#### Mounting Method:

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

8 single actuator

#### Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-459-5693

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

## **Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

## Style Designator:

Circular wafer, bushing mount

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0