

View Online at <https://aerobasegroup.com/nsn/5930-00-459-5701>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.380 inches single mounting facility

**Overall Length:**

1.762 inches

**Overall Height:**

1.250 inches

**Overall Width:**

1.310 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.216 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.940 inches single actuator

**Nonturn Device Radius:**

0.530 inches at 9: 00 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Tab at 9: 00 o'clock

**Operating Temperature Range:**

-18.0/+52.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

2 single section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

45.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

60.0 degrees single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0