

View Online at <https://aerobasegroup.com/nsn/5930-00-460-1698>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.781 inches

Body Width:

0.250 inches

Body Height:

0.359 inches

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Diameter:

0.046 inches

Actuator Height:

0.065 inches

Actuator Free Position Height:

0.360 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

Between 3.0 ounces and 5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 printed circuit or 3 wire loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0