NSN 5930-00-460-7884

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-460-7884

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

2.749 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Overall Diameter:

1.188 inches

Nonturn Device Radius:

0.375 inches at 3: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at altitude

NSN 5930-00-460-7884

Rotary Switch - Page 2 of 2



| Sty | ما | D | 20 | in | n | 2 | ŧ۸ | r | |
|-----|----|----|----|----|----|---|----|---|--|
| JLY | ı | יש | င၁ | ıу | •• | а | ιυ | ш | |

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0