

View Online at <https://aerobasegroup.com/nsn/5930-00-460-8910>

Body Style:

Bushing mounted

Body Diameter:

Between 0.985 inches and 1.015 inches

Bushing Length:

Between 1.345 inches and 1.405 inches

Body Length:

0.980 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

Between 1.240 inches and 1.305 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

Between 96.0 ounces and 192.0 ounces

Actuator Movement:

Between 0.040 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Unf

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0