# NSN 5930-00-461-2567

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-461-2567

# Thread Class:

2a single mounting facility

## Thread Length:

0.469 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

2.969 inches

#### First Flat Length:

0.750 inches single actuator

#### Flat Height:

0.219 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

## 0.969 inches single actuator

**Overall Diameter:** 

#### 2.000 inches

Individual Section Quantity:

2

Knob Manufacturer Code:

82121

Knob Manufacturer Part Number:

А

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

2 each section rear

## Throw Quantity:

3 each section rear

## **Mounting Method:**

Threaded bushing single mounting facility

#### **Features Provided:**

Actuator knob

## Thready Qty Per Inch (tpi):

32 single mounting facility

## **Thread Size:**

0.469 inches single mounting facility

# **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

3 single actuator

# NSN 5930-00-461-2567

Rotary Switch - Page 2 of 2



Shaft Type:

Round, flatted, threaded hole single actuator

**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Breaks before makes each section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load dc at sea level

#### Precious Material And Location:

Contact surfaces silver

**Precious Material:** 

Silver

## Style Designator:

Tap, circular, bushing mount

# **Thread Series Designator:**

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A052b0