NSN 5930-00-461-7840

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-461-7840

| Body Style: |
|---|
| Hole mounted |
| Overall Length: |
| 4.000 inches |
| Overall Height: |
| 6.755 inches |
| Overall Width: |
| 4.750 inches |
| Case Material: |
| Metal |
| Actuator Style: |
| Roller arm |
| Actuator Height: |
| 1.580 inches |
| Actuator Roller Diameter: |
| 0.750 inches |
| Actuator Roller Width: |
| 0.250 inches |
| Housing Height: |
| 5.600 inches |
| Housing Length: |
| 4.000 inches |
| Housing Width: |
| 4.000 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Height: |
| 2.375 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 2.375 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 16.0 ounces |
| Switch Actuating Force: |
| 114.0 ounces |
| Actuator Movement: |
| Between 12.0 pretravel degrees and 45.0 overtravel degrees and 5.0 differential degrees |

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

NSN 5930-00-461-7840

Sensitive Switch - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 6 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Domilitarization |

Demilitarization:

No

Fiig:

A053a0