NSN 5930-00-462-0607

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-462-0607

Thread Class:					
2a all threaded stud					
Thread Length:					
0.375 inches all threaded stud					
Overall Height:					
0.953 inches					
Body Height:					
0.406 inches					
Overall Diameter:					
0.625 inches					
Tempurature Sensing Element Type:					
Internal sensor					
Mounting Method:					
Threaded stud					
Thready Qty Per Inch (tpi):					
32 all threaded stud					
Contact Action Stimulus:					
Increase					
Thread Size:					
0.138 inches all threaded stud					
Nonpile-up Contact Arrangement:					
Nonplie-up Contact Arrangement.					
1 pole, single throw, normally closed, momentary action					
1 pole, single throw, normally closed, momentary action					
1 pole, single throw, normally closed, momentary action Terminal Type:					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating:					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability:					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating:					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts:					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz:					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed:					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas or liquid					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas or liquid Style Designator:					
1 pole, single throw, normally closed, momentary action Terminal Type: Tab, solder lug Contact Load Current Rating: 1.0 amperes resistive load single voltage Contact Adjustability: Deactuation point not adjustable and actuation point not adjustable Contact Stimulus Rating: 155.00 actuation point degrees fahrenheit Contact Voltage Rating In Volts: 115.0 ac at sea level single voltage Frequency In Hertz: 60.0 single voltage Media For Which Designed: Gas or liquid Style Designator: Disc					

N/a

NSN 5930-00-462-0607

Thermostatic Switch - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A048b0