

View Online at <https://aerobasegroup.com/nsn/5930-00-463-3059>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.605 inches and 0.615 inches

**Body Length:**

Between 0.468 inches and 0.473 inches

**Body Width:**

Between 0.120 inches and 0.130 inches

**Body Height:**

Between 0.355 inches and 0.365 inches

**Unthreaded Mounting Hole Diameter:**

0.095 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.047 inches and 0.079 inches

**Actuator Height:**

Between 0.151 inches and 0.161 inches

**Housing Length:**

0.468 inches

**Housing Width:**

0.140 inches

**Maximum Voltage Rating In Volts:**

50.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

20.0 grams

**Switch Actuating Force:**

40.0 grams

**Actuator Movement:**

0.015 overtravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 milliamperes inductive dc

**Special Features:**

No. 0-80 socket head screw @supplied

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0