

View Online at <https://aerobasegroup.com/nsn/5930-00-463-3116>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.373 inches and 0.377 inches

Body Length:

Between 0.771 inches and 0.791 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.349 inches and 0.369 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

0.040 inches

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0