NSN 5930-00-463-5264

Thermostatic Switch - Page 1 of 2

Contact Voltage Rating In Volts: 28.0 dc at sea level second voltage

Overall Length: 1.310 inches



View Online at https://aerobasegroup.com/nsn/5930-00-463-5264

Overall Height:
0.590 inches
Overall Width:
0.400 inches
Body Length:
0.750 inches
Body Height:
0.340 inches
Unthreaded Mounting Hole Diameter:
0.115 inches
Distance Between Mounting Facility Centers:
1.031 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
125.0 degrees celsius and -65.0 degrees celsius
Mounting Method:
Bracket and unthreaded hole
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab, solder lug
Contact Load Current Rating:
5.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+28.00/+77.00 actuation point degrees celsius and +28.00/+77.00 deactuation point degrees celsius
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:
77.00 actuation point degrees celsius and 75.00 deactuation point degrees celsius and 3.00 differential point degrees celsius

NSN 5930-00-463-5264 Thermostatic Switch - Page 2 of 2



Frequency In Hertz:
60.0 first voltage
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Case surface gold
Precious Material:
Gold
Style Designator:
Rectangular w/bracket
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0