

View Online at <https://aerobasegroup.com/nsn/5930-00-464-4123>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.440 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Dustproof and explosion proof

**Overall Length:**

2.250 inches

**First Flat Length:**

0.450 inches single actuator

**Flat Height:**

0.450 inches single actuator

**Shaft Diameter:**

0.249 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Overall Diameter:**

1.330 inches

**Individual Section Quantity:**

1

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

5 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Rotor Through Connection Quantity:**

1 single section

**Switch Actuator Indexing Position Quantity:**

5 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load ac at sea level

**Precious Material And Location:**

Contact silver

**Precious Material:**

Silver

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Uns single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0