

View Online at <https://aerobasegroup.com/nsn/5930-00-464-4128>

Inside Diameter:

0.375 inches single connection

Hazardous Locations/environmental Protection:

Dust resistant and moisture resistant

Overall Length:

3.500 inches

Overall Height:

7.000 inches

Overall Width:

2.500 inches

Body Height:

3.500 inches

Unthreaded Mounting Hole Diameter:

0.266 inches

Longest Horizontal Distance Between Mounting Centers:

2.719 inches

Longest Vertical Distance Between Mounting Centers:

2.719 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

3500.00 pounds per square inch

Thread Size:

0.375 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

6.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.00/+1000.00 actuation point pounds per square inch and -35.00/+865.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw and external deactuation point screw

Contact Voltage Rating In Volts:

600.0 ac at sea level fourth voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0