## NSN 5930-00-464-6968

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-464-6968

| Body Style:  |
|--|
| Panel mount  |
| Overall Length:  |
| 1.250 inches   |
| Overall Height:  |
| 2.388 inches   |
| Overall Width:   |
| 1.000 inches   |
| Body Length:   |
| 0.905 inches   |
| Body Width:  |
| 0.655 inches   |
| Actuator Length:   |
| 0.840 inches   |
| Actuator Style:  |
| Rectangular  |
| Actuator Height:   |
| 0.430 inches   |
| Actuator Width:  |
| 0.590 inches   |
| Actuator Color:  |
| White single actuator  |
| Illuminated Actuator Color:  |
| White single actuator  |
| Actuator Inscription:  |
| Range enter single actuator  |
| Maximum Voltage Rating In Volts:   |
| 250.0 ac and 28.0 dc   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Panel  |
| Features Provided:   |
| Holding solenoid   |
| Nonpile-up Contact Arrangement:  |
| 4 pole, double throw, one position momentary single switch unit                          |
| Contact Load Current Rating At Maximum Rated Voltage:                                    |
| 3.000 amperes resistive dc and 1.500 amperes inductive dc and 2.000 amperes resistive ac |
| Special Features:  |
| Three terminals included for lamp  |

**Terminal Type And Quantity:** 

15 tab, solder lug

## NSN 5930-00-464-6968

Push Switch - Page 2 of 2



| C | ha  | Ιf | 1 | ife   |  |
|---|-----|----|---|-------|--|
| • | ııe |    | _ | .II C |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0